



Vacuum packing machine SE-604 230-400/50/3N


TECHNICAL SPECIFICATIONS

Pump capacity: 40 m³/h
 Bar length: 413 mm + 656 mm
 Total loading: 1100 W
 Vacuum pressure (maximum): 0.5 mbar

Electrical supply: 230 V-400 V / 50 Hz / 3 ~ (7.3 A)

Internal dimensions

·Width: 672 mm
 ·Depth: 481 mm
 ·Height: 200 mm

External dimensions (WxDxH)

·Width: 740 mm
 ·Depth: 566 mm
 ·Height: 997 mm

Net weight: 145 Kg
 Noise level (1m.): 75 dB(A)
 Background noise: 32 dB(A)

DEFAULT EQUIPMENT

- Sensor Controls
- Up to 10 seconds of extra vacuum pull
- Soft air function
- Dry oil cycle
- BUSCH pump
- NSF Approved
- Clear methacrylate lid
- Filling plate

OPTIONAL EQUIPMENT

- Vacuum packing bags
- External vacuum kit for Vac-Norm, containers and accessories
- Bag cutting kit
- Support for liquid packaging
- Additional filling plates



Vacuum packing machine SE-604 230-400/50/3N

FLOORSTANDING UNIT. 40 M³/H. 413+656 MM.

Two sealing bars (413+656 mm.)
40 m³/h Busch vacuum pump.
Vacuum controlled by sensor.

- Powered by Busch.
- Vacuum controlled by sensor.
- Vacuum PLUS.
- Digital keyboard.
- Control panel equipped with display indicating the exact vacuum percentage.
- "Pause" button to marinate food.
- Safe liquid packing thanks to sensor control.
- Double seal.
- Cordless sealing bar.
- Bag-sealing programme.
- Pulse-controlled decompression.
- Vac-Norm ready with Automatic decompression.
- Stainless steel body and chamber.
- Damped transparent lid of highly durable polycarbonate.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- Safety system with protection against vacuum failure.
- NSF-listed.



SAMMIC, S.L.
Basarte, 1 - 20720 AZKOITIA
www.sammic.com

