



## Vacuum packing machine SU-604GP 230-400/50/3N



### TECHNICAL SPECIFICATIONS

Pump capacity: 40 m<sup>3</sup>/h  
 Bar length: 413 mm + 656 mm  
 Total loading: 1100 W  
 Vacuum pressure (maximum): 0.5 mbar

Electrical supply: 230 V->[v:002\_tension2]</font> / 50 Hz / 3 ~ (7.3 A)

#### Internal dimensions

- Width: 672 mm
- Depth: 481 mm
- Height: 200 mm

#### External dimensions (WxDxH)

- Width: 740 mm
- Depth: 566 mm
- Height: 997 mm

Net weight: 145 Kg  
 Noise level (1m.): 75 dB(A)  
 Background noise: 32 dB(A)

#### DEFAULT EQUIPMENT

- Filling plate
- Inert gas flush
- Bluetooth connectivity
- Printer connection

#### OPTIONAL EQUIPMENT

- Printer
- Vacuum packing pouches
- Vac-Norm external vacuum kit, containers and accessories
- Bag cutting kit
- Support for liquids
- Additional filling plates



## Vacuum packing machine SU-604GP 230-400/50/3N

FLOORSTANDING UNIT. 40 M<sup>3</sup>/H. 413+656 MM.

Two sealing bars (413+656 mm.)  
40 m<sup>3</sup>/h Busch vacuum pump.  
Vacuum controlled by sensor.

- Powered by Busch.
- Vacuum controlled by sensor.
- Vacuum PLUS.
- LCD colour screen: all information at a glance.
- Backlit touch keyboard.
- Programmable: 25-programme memory. Blocking option.
- "Pause" button.
- Phased vacuum programme.
- Detection of the evaporation of liquids.
- Double seal.
- Cordless sealing bar.
- Progressive decompression.
- Vac-Norm ready with Automatic decompression.
- Stainless steel body and chamber.
- Damped transparent lid of high durability polycarbonate.
- Dry-oil programme for drying the pump.
- Working hours counter for oil changes.
- Safety system with protection against vacuum failure.
- NSF-listed.



ER-4437/196 UNE-EN ISO 9001

SAMMIC, S.L.  
Basarte, 1 - 20720 AZKOITIA  
www.sammic.com

