



+70/-40 °C



ASR15



+70/-40 °C

Abbattitore e surgelatore rapido

blast chiller shock freezer | cellule de refroidissement rapide | schnellkühler schock-froster | abatidor rapido



		°C			lt	kw	cm	Kg	cm	Kg	€
ASR3		14/1		GN1/1 x3 0 40x60 x3	1,15	↔ 75 ↗ 74 ↓ 76	50	↔ 78 ↗ 77 ↓ 92	58		
		11/1									
ASR5		20/1		GN1/1 x5 0 40x60 x5	1,42	↔ 75 ↗ 74 ↓ 86	71	↔ 78 ↗ 77 ↓ 105	80		
		15/1									
ASR7		25/1		GN1/1 x7 0 40x60 x7	1,49	↔ 75 ↗ 74 ↓ 126	110	↔ 78 ↗ 77 ↓ 105	122		
		20/1									
ASR10		35/1		GN1/1 x10 0 40x60 x10	1,60	↔ 75 ↗ 74 ↓ 126	115	↔ 78 ↗ 77 ↓ 143	125		
		25/1									
ASR15		45/1		GN1/1 x15 0 40x60 x15	1,8	↔ 75 ↗ 74 ↓ 185	130	↔ 78 ↗ 77 ↓ 202	142		
		35/1			380V						
ASR20		50/1		GN1/1 x20 0 40x60 x20	2,04	↔ 75 ↗ 74 ↓ 208	155	↔ 78 ↗ 77 ↓ 225	170		
		40/1			380V						



Optionals

optionals | optionals | extra | opciones

220V/60Hz

115V/60Hz

+ 5%