



+70/-40 °C



ASR3



ASR5



+70/-40 °C

Abbattitore e surgelatore rapido

blast chiller shock freezer | cellule de refroidissement rapide | schnellkühler schock-froster | abatidor rapido



			°C		lt	kw	cm	Kg	cm	Kg	
ASR3				14/1	GN1/1 x3 o 40x60 x3	1,15	↔75 ↗74 ↓76	50	↔78 ↗77 ↓92	58	
				11/1							
ASR5				20/1	GN1/1 x5 o 40x60 x5	1,42	↔75 ↗74 ↓86	71	↔78 ↗77 ↓105	80	
				15/1							
ASR7				25/1	GN1/1 x7 o 40x60 x7	1,49	↔75 ↗74 ↓126	110	↔78 ↗77 ↓105	122	
				20/1							
ASR10				35/1	GN1/1 x10 o 40x60 x10	1,60	↔75 ↗74 ↓126	115	↔78 ↗77 ↓143	125	
				25/1							
ASR15				45/1	GN1/1 x15 o 40x60 x15	1,8	↔75 ↗74 ↓185	130	↔78 ↗77 ↓202	142	
				35/1		380V					
ASR20				50/1	GN1/1 x20 o 40x60 x20	2,04	↔75 ↗74 ↓208	155	↔78 ↗77 ↓225	170	
				40/1		380V					



Optionals

optionals | optionals | extra | opciones

220V/60Hz

115V/60Hz

+ 5%