



+70/-40 °C

Abbattitore e surgelatore rapido

blast chiller shock freezer | cellule de refroidissement rapide | schnellkühler schock-froster | abatidor rapido



		°C			lt	kw	cm	Kg	cm	Kg	€
ASR3			14/1		GN1/1 x3 0 40x60 x3	1,15	↔ 75 ↗ 74 ↓ 76	50	↔ 78 ↗ 77 ↓ 92	58	
			11/1								
ASR5			20/1		GN1/1 x5 0 40x60 x5	1,42	↔ 75 ↗ 74 ↓ 86	71	↔ 78 ↗ 77 ↓ 105	80	
			15/1								
ASR7			25/1		GN1/1 x7 0 40x60 x7	1,49	↔ 75 ↗ 74 ↓ 126	110	↔ 78 ↗ 77 ↓ 105	122	
			20/1								
ASR10			35/1		GN1/1 x10 0 40x60 x10	1,60	↔ 75 ↗ 74 ↓ 126	115	↔ 78 ↗ 77 ↓ 143	125	
			25/1								
ASR15			45/1		GN1/1 x15 0 40x60 x15	1,8	↔ 75 ↗ 74 ↓ 185	130	↔ 78 ↗ 77 ↓ 202	142	
			35/1			380V					
ASR20			50/1		GN1/1 x20 0 40x60 x20	2,04	↔ 75 ↗ 74 ↓ 208	155	↔ 78 ↗ 77 ↓ 225	170	
			40/1			380V					



Optionals

optionals | optionals | extra | opciones

220V/60Hz

115V/60Hz

+ 5%

+70/-40 °C